

The Skid Mounted HVAC System offers all-in-one services for air conditioning, area cooling, dehumidifying, and portable heating needs. Completely self-contained and portable, this unit provides 3.5 tons/42,000 Btu per hour of cooling and heating.

Key Features and Benefits

- Up-fitted Trane® combination heat pump for reliable performance
- Wrap-around coil guard increases moisture removal of A/C units, dryer supply ducts, humidity control, and energy savings through passive reheat
- Over/under ducting design for efficient direct connection with removable filter
- · Cost effective no fan belts to replace
- · Internally insulated cabinet for quiet operation
- On board thermostat for temperature control
- · Baked-on powder coated finish for long lasting coverage
- · Easy to remove, built in filter housing to allow for easy filter replacement

Standard Components

- · HVAC Unit
- · Powder Coated Skid
- 11.52 kW Heat Strip
- •16 x 25 x 1" Filter
- $\boldsymbol{\cdot} \, \text{On Board Thermostat}$
- 8' Power Cord With L6-30P End
- · Condensation Runoff Drain System

CL-ACXE1200LC Specifications NSN Pending

| Dimensions | 55 x 35 x 36" | (1.4 x 0.88 x 0.91 m) |
|-------------------------------|-----------------------|------------------------|
| Cube | 40.1 ft ³ | (1.13 m ³) |
| Weight | 425 lbs | (192.7 kg) |
| Rated | 208/240 Volts, 30-Amp | Single-Phase, 60 Hertz |
| CFM | 1,400 | |
| Cooling | 42,000 Btu/hr | |
| Heating | 40,000 Btu/hr | |
| XE12UD Supply Boot | 12" | (30.5 cm) |
| XE12UD Return Boot | 14" | (35.5 cm) |
| XE12LD Replaceable Filter | 16" x 25" x 1" | (40.6 x 63.5 x 2.5 cm) |
| Standard Supplemental Heating | | |

anuaru suppremental nearing

27/36k Btu/hr (For use when ambient temperature is below 40° F (4.5° C) and requires 50 amp circuit for operation



