



Features and Benefits

- · Compact to store and handle
- · Easily assembled without tools
- Fully-functional with or without privacy walls
- Provides maximum coverage without large volume of water

HZ-DS1 Specifications

Dimensions	60 x 60 x 84"	(18.3 x 18.3 x 25.6 m)
Packaged Dimensions	64 x 14 x 21''	(19.5 x 4.3 x 6.4 m)
Weight	102 lbs	(46.3 kg)
Speed	3.5 GPM (gallons per minute) @ 50 PSI 4.5 GPM (gallons per minute) @ 75 PSI	

Components

- · Articulated mainframe and roof truss: constructed of bright plated thin wall steel with yellow powder coated finish
- 5' x 5' x 6" single-compartment, freestanding flexible fabric primary containment pool with 3/4" GHT drain fittings
- Complete fabric frame cover with two zippered entrance/exit doors
- Four unique, horizontal, magnet mounted spray nozzles can be placed at any height on the shower frame or individually pulled off to serve as a hand held nozzle. One fixed, wide cone overhead nozzle
- Supply side pigtail with master shut-off
- Rugged, heavy duty, zippered carry bag
- Optional 3' x 3' Elevated Flexible Matting Optional 110V Electric Sump Pump Kit with protective case
- Primary containment basin: freestanding flexible fabric
- Frame cover: 14 oz. reinforced vinyl
- · Roof cover: 14 oz. reinforced vinyl, semi-clear skylight
- · Cover color: Desert Sand



