



SENTINEL AIRFRAME™ I SYSTEM

Sentinel Airframe™ I System Key Features:

- Ready for use in under 4 minutes
- Built-in electrical inflator
- Modular inflatable frame with double inflation/deflation valves and over-pressure valves
- Wide opening doors with triple zippers and water barrier
- Pre-fitted docking zippers around doors
- Heavy-duty and non-slip PVC coated removeable fabric floor, allows shelter to be picked up and placed over accident scene when fully inflated
- 4 windows, 3-way system with both mesh and clear PVC covers
- Integrated internal LED lighting
- 2 duct openings, one on each side, for HVAC unit
- Equipment hanging loops
- Pre-fitted guy ropes
- Modular design allows multiple shelters to connect in any direction.
- Constructed of durable, fire and UV resistant PVC coated fabric
- Roto-molded stackable hard case

Specifications

Part #	Sentinel I SW-SI3W (White) SW-SI3O (Orange)	Sentinel I-L SW-SIL3W (White) SW-SIL3O (Orange)
Dimensions	15'1" x 13'1" x 9'2"	15'1" x 19'4" x 9'2"
Useable footage	172 sq ft	258 sq ft
Weight	156 lbs	172 lbs
Number arches	3	4
Colors	White, Orange	White, Orange
Case dimensions	45" x 45" x 29"	45" x 45" x 29"
Set-up time	3 min	4 min

Sentinel Airframe™ I System Options

Connecting corridor	SO-VCSIW (White)	SO-VCSIO (Orange)
---------------------	------------------	-------------------