C2 COMMUNICATIONS TABLES

Part Number AV- SOCLST5 | AV- SOCLST6 | AV- SOCLSTC AV- SOCLST5.31 | AV- SOCLST6.31 | AV- SOCLST5.170 | AV- SOCLST6.170 Pre-Wired Communications Tables



ISO 9001:2008 Registered Company



S

I

ļ

1

ļ

A

A

Made from lightweight, rugged aluminum, tables are pre-wired for power, classified and unclassified data networks, voice and video distribution. Standard Communications Tables come in lengths of 5 and 6 feet and corner table.

With integrated wiring and daisy-chaining C2 Communication Tables significantly reduce cable management issues and reduce setup/strike time and costs in both deployable and fixed TOCs/EOCs.

Key Features and Benefits

- · Ultra-durable, extruded aluminum table prewired for networks, voice, and video distribution
- Numerous table arrangement capabilities
- · Storage and transit options include rugged, aluminum cases or economical padded bags

Standard Components

- Data and Power Tables: 5 ft, 6 ft in length, corner table, 24 in deep, lightweight, integrated 120 VAC power, one TCP/IP switched data networks (8-port 10/100/1000, 4 - Port PoE unamanged), VGA-based video distributions network. Includes one 12 ft. power cable
- · Standard Table: 5 ft., 6ft. in length, corner table, 24 in deep, lightweight, channel brackets on table bottom to manage power, data, and video cable home runs

GSA	Schedule	ISO



A	1 ARAMAN		
pe	cifications		
AV-	SOCLST5	5' X 24", Standard	
	Packaged Dimensions	60" x 24" x 2.88	(1.5 x .6 x .07 m)
	Deployed Dimensions	60" x 24" x 29.74"	(1.5 x .6 x .75 m)
	Weight	30 lbs	(13.6 kg)
AV-	SOCLTS6	6' x 24", Standard	
	Packaged Dimensions	72" x 24" x 2.88"	(1.8 x .6 x .07 m)
	Deployed Dimensions	72" x 24" x 29.75"	(1.8 x .6 x .75 m)
	Weight	35 lbs	(15.8 kg)
AV-	SOCLSTC	Corner Standard	
	Packaged Dimensions	60" x 24" x 2.88"	(1.5 x .6 x .07 m)
	Deployed Dimensions	60" x 24" x 29.75"	(1.5 x .6 x .75 m)
	Weight	26 lbs	(11.8 kg)
AV-	SOCLST5.31	5' x 24", Power	
	Packaged Dimensions	60" x 24" x 2.88"	(1.5 x .6 x .07 m)

AV-	SOCLSTC	Corner Standard	
	Packaged Dimensions	60" x 24" x 2.88"	(1.5 x .6 x .07 m)
	Deployed Dimensions	60" x 24" x 29.75"	(1.5 x .6 x .75 m)
	Weight	26 lbs	(11.8 kg)
AV-	SOCLST5.31	5' x 24", Power	
	Packaged Dimensions	60" x 24" x 2.88"	(1.5 x .6 x .07 m)
	Deployed Dimensions	60" x 24" x 29.75"	(1.5 x .6 x .75 m)
	Weight	35 lbs	(15.8 kg)
AV-	SOCLST6.31	6' x 30", Power	
	Packaged Dimensions	72" x 24" x 2.88"	(1.8 x .6 x .07 m)
	Deployed Dimensions	72" x 24" x 29.75"	(1.8 x .6 x .75 m)
	Weight	40 lbs	(18.1 kg)
AV-	SOCLST5.170	5'x 24", Data/Power	
	Packaged Dimensions	60" x 24" x 5.88"	(1.5 x .6 x .75 m)
	Deployed Dimensions	60" x 24" x 29.75"	(1.5 x .6 x .75 m)
	Weight	47 lbs	(21.3 kg)
AV-	SOCLST6.170	6' x 24", Data/Power	
	Packaged Dimensions	72" x 24" x 5.88"	(1.8 x .6 x .15 m)
	Deployed Dimensions	72" x 24" x 29.75"	(1.8 x .6 x .75 m)
	Weight	52 lbs	(23.5 kg)