

# VIDEO DISTRIBUTION UNIT

Part Number AV-SOVDU

Control Multiple Video Inputs / Outputs With One Device



ISO 9001:2008 Registered Company



## Key Features and Benefits

- Video / Audio switching system support
- Video Inputs: Five HD-15 VGA, one composite and one HDMI inputs
- Video Outputs: Four HD-15 VGA outputs
- One multi-image processor capable of displaying up to four separate video/image sources through a single projector or TV / monitor.
- Each of these image windows can be resized, moved, and named.
- Audio system supports two XLR microphones and one line level inputs and two line level outputs
- VDU System operates off of 120 VAC and all components are plugged into an uninterrupted power source (UPS)
- The VDU system is controlled by a touch-panel display or by a browser-based Graphical User Interface (GUI)
- All components mounted inside a rugged, weather-resistant, shock-mitigating case

## Standard Components

- Video/Audio switching system supporting five (5) HD-15 VGA, one (1) composite and one (1) HDMI inputs and four (4) HD-15 VGA output
- All components mounted inside a rugged, weather-resistant, shock-mitigating case.

## AV-SOVDU Specifications

|                     |                      |                        |
|---------------------|----------------------|------------------------|
| 1 Case Dimensions   | 36.8 x 27.5 x 20.5"  | (0.9 x 0.7 x 0.5 m)    |
| Cube                | 11.3 ft <sup>3</sup> | (0.3 m <sup>3</sup> )  |
| 1 Case Dimensions   | 16 x 13 x 6.9"       | (0.4 x 0.3 x 0.2 m)    |
| Cube                | 0.7 ft <sup>3</sup>  | (0.02 m <sup>3</sup> ) |
| Deployed Dimensions | 36.8 x 18.5 x 20.5"  | (0.9 x 0.5 x 0.5 m)    |
| Weight              | 122 lbs              | (55.4 kg)              |

