



MIL-SPEC HVAC

Features and Benefits

- All-in-one services for air conditioning, dehumidifying and heating
- Completely self-contained and portable
- Hot Gas Bypass
- Phase Protection
- Remote Controls
- EMI Suppression
- Stackable
- External Service Ports
- Staggered Start - Compressor Only
- Elapsed time Indicator
- Service Outlet
- Duct Covers
- Fork Pockets and Lifting Eyes
- Optional Casters
- Available as a stacking unit, allowing multiple devices to be easily stacked upon transport

Standard Components

- HVAC Unit
- 11.52 kW Heat Strip
- 16 x 25 x 1" Filter
- Electronic Thermostat
- Thermostat Cable
- Connector Cord

CL-ACT65T Specifications

Dimensions	52 x 42 x 30"	(1.3 x 1 x 0.7 m)
Weight	500 lb	(226.8 kg)
Cooling Capacity	60,000 BTU/HR	
CFM	2,000 CFM Min. @1" ESP	
Heating Capacity	10 kW	
Max Operating Ambient	+140 °F	(+60 °C)
Rating Ambient	+125 °F	(+51 °C)
Min Operating Ambient	-40 °F	(-40 °C)
Refrigeration Stages	1	
Compressor Type	Scroll	
Refrigerant Type	R-407C	
Evaporator Coil	Copper Tube / Aluminum Fin	
Condenser Coil	Microchannel Aluminum	
Duct Connections	Supply 16" Diameter	Return 16" Diameter
Voltage / Phase/ HZ	380 / 3 / 50, 5 Wire	
Max Power Draw	12 kW	
Heating stages	2 Stages	
Frame and Panel Material	5052 Aluminum	