



HVAC



Features and Benefits

- Up-fitted Trane® combination heat pump for reliable performance
- Wrap-around coil guard increases moisture removal of A/C units, dryer supply ducts, humidity control, and energy savings through passive reheat
- Over/under ducting design for efficient direct connection with removable filter
- Cost effective - no fan belts to replace
- Internally insulated cabinet for quiet operation
- Full tube frame with lifting bars for easy transport
- Baked-on powder coated finish for long lasting coverage
- Remote thermostat with 50' cord to allow for proper installation with in the shelter
- Easy to remove, built in filter housing to allow for easy filter replacement
- Available as a stacking unit, allowing multiple XE-1200 devices to be easily stacked upon transport

Standard Components

- HVAC Unit
- 11.52 kW Heat Strip
- 16 x 25 x 1" Filter
- Electronic Thermostat
- Thermostat Cable
- Connector Cord
- Caster Tech Lock Brake Kit
- Vinyl Cover
- Connection Boots
- 50' Power Cord
- Condensation Runoff Drain System
- Hvac Stackable Cart (Optional)

CL-ACXE1200 Specifications

Dimensions	56 x 35 x 41.5"	(1.4 x 0.9 x 1 m)
Weight	526 lb	(238.5 kg)
Cube	48.5 ft	(14.8 m)
Rated	208/240 Volts, 30-Amp	Single-Phase, 60 Hertz
CFM	1,400	
Cooling	42,000 Btu/hr	
Heating	40,000 Btu/hr	
Ducting		
XE12UD Supply Boot	12"	(30.5 cm)
XE12UD Return Boot	14"	(35.5 cm)
XE12UD Return Filter	16" x 25" x 1"	(40.6 x 63.5 x 2.5 cm)

Standard Supplemental Heating

27/36k Btu/hr (For use when ambient temperature is below 40° F (4.5° C) and requires 50 amp circuit for operation)

Remote Thermostat with 50' (15.3 m) cord controls both standard HVAC and aux heat