



AIR DISTRIBUTION PLENUMS



Features and Benefits

- Powerful fan system allows the heater to deliver uncontaminated heat to your shelter or duct system
- Runs on a variety of fuels including: kerosene, diesel, JP8 and Jet A/B
- Lightweight, portable design
- Low maintenance
- Thermostat for constant temperature control
- Heat for one WS/GK-1935 shelter or for two WS/GK-20 shelters
- Heat exchanger to keep exhaust gas and heated air separate
- Large capacity diesel fuel tanks provide hours of continuous operation

Standard Components

- One 91,000 Btu, Indirect-Fired, Trifuel Heater
- Remote room thermostat

CL- HT1000 Specifications

Dimensions	(49.3 x 20 x 30.5")	(1.25 x 0.5 x 0.77m)
Weight	94lbs	42 kg
Heat Input	110 kBTU/h	
Heat Output	91.9 kBTU/h	
Air Flow	880 cfm	
Fuel Type	Diesel/Kerosene	JP8 and Jet A/B
Power Supply	120 v, 60Hz	
Electric Usage	520 W, 5.76 A	
Fuel Usage	.80 g/h	5.53lb/h
Tank Capacity	10.8 gallons	40.9 liters
Pump Pressure	167 PSI	
Max Temp. Air Duct	250° F	
Flue Diameter	5.9in	15cm

