

MQ POWER 1 PHASE GENERATORS

Part Number EL-GN15SPXU4F | EL-GN20SPXU4F | EL-GN36SPXU4F

Portable Power To Fit Your Mission



ISO 9001:2008 Registered Company



The MQ Power WhisperWatt™ line of portable generators provides a variety of power options to suit the needs of your mission. Each WhisperWatt™ generator features a sound-deadening, weather-resistant housing that allows substantially lower operating noise levels than competitive designs.

An automatic safety shutdown system monitors the water temperature, engine oil pressure, low coolant, low DEF, overspeed, and overcrank. Warning lights indicate abnormal conditions.

The fully covered power panel allows fast and convenient hookup for most applications including temporary power boxes, tools and lighting equipment. All are NEMA standard.

Key Features and Benefits

- Heavy duty 4-cycle, direct injection, turbocharged, charge air cooled diesel engine provides maximum reliability
- Brushless alternator reduces service and maintenance requirements
- Shock welding to steel frame for minimum vibration and extended service life.
- Weather-resistant steel housing for durability
- Sound proofing enables operation as low as 64 dBA full load at 23 ft.
- Automatic safety shutdown system
- Meets Tier 4 EPA emissions standards
- Internal fuel tank with direct reading fuel gauges
- Illuminated, easy-to-read instrument panels
- Fully lockable enclosure for safe, unattended operation
- Transport options include trailers and wheel kits for complete mobility

Specifications

Part Number	EL-GN15SPXU4F	EL-GN20SPXU4F	EL-GN36SPXU4F
Engine	Kubota Tier 4 Final	Isuzu Tier 4 Final	Kubota Tier 4 Final
Output	15 Kw	20 Kw	36 Kw
Dimensions	56.3 x 35.4 x 25.6" (1430 x 900 x 650 mm)	71.65 x 31.10 x 49.61" (1820 x 790 x 1260 mm)	87.01 x 37.40 x 61.02" (2210 x 950 x 1550 mm)
Weight (Dry)	1,179 lbs (535 kg)	1,797 lbs (815 kg)	2,448 lbs (1,110 kg)
Cube	29.52 ft ³ (0.83 m ³)	63.97 ft ³ (1.8 m ³)	114.9 ft ³ (3.25 m ³)
Fuel Consumption	1.09 gph at full load	1.62 gph at full load	2.93 gph at full load
Fuel Capacity	16.4 gallons (62 L)	17 gallons (64.3 L)	26.5 gallons (100.3 L)
Decibels at 23 ft	64 dBA	65 dBA	66 dBA
Fits Trailer	EL-GNTRLAMPXF		

