

The HZ-DS3LSII-4 DECON System is a fast deployment three lane, four station inflatable mass decontamination shower.

The shower system is capable of handling three parallel lines of casualties at the same time passing four stations: undress area, detergent shower, rinse shower and redress area.

The undress and redress areas are dry areas. Shower stations are placed above a built-in waste water storage basin with a raised grid floor. Both outer lanes have three fixed spray nozzles per detergent and rinse station. The middle lane has two spray nozzle guns on a coiled hose line for soaping and two for rinsing. In total the decontamination shower system has sixteen discharge points.


### **Key Features and Benefits**

- Fast deployment, ready for use in 4 minutes
- · 3 lanes handle 3 parallel lines of casualties simultaneously
- · 4 stations, 1 shelter: undress, detergent shower, rinse shower and redress
- Dry undress and redress areas with overlapping curtains for privacy
- Shower stations located above a waste water storage basin with a raised grid floor safely catches grey water
- Outer lanes have 3 fixed spray nozzles per detergent and rinse station
- · Center lane has 2 spray nozzle guns on a coiled hose for soaping and rinsing
- · Shower groups connect to water supply via quick connection couplings
- · Waste water storage basin holds over 250 gallon/1000 liters, pump removes excess water
- PVC coated canopy and divider curtains remove for easy cleaning or replacement
- · Undress stations have a pass-through chute for clothing
- 4 skylights eliminate need for interior lighting
- All air beams, cover and floor are constructed of heavy-duty PVG coated polyster, high-frequency welded for strength and durability

### **Standard Components**

- · High-pressure inflation valve kit
- · Waste water pump
- · 11 plastic grid panels
- · Protective ground cover
- · Anchoring kit
- · Repair kit

#### **HZ-DS3LSII-4 Dimensions**



MILITARY INDUSTRIAL FIRST RESPONDER MEDICAL HOMELAND SECURITY EVENTS

# **DECON SYSTEM**

Part Number <del>HZ-</del>DS3LSII-4 Inflatable Shower Handles 80 Persons Per Hour



## **HZ-DS3LSII-4 Specifications**

Shelter Dimensions         24'11" x 17'9" x 8'6"         (7.6 x 5.4 x 2.6 m)           Door Dimensions         3'11" x 6'1"         (1 x 2.1 m)           Undress Dimensions         98 x 59"         (250 x 150 cm)           Detergent Dimensions         49" x 59"         125 x 150 cm)           Rinse Dimensions         49" x 59"         (250 x 150 cm)           Redress Dimensions         98" x 59"         (250 x 150 cm)           Airframe Diameter         14" )         (35 cm           Working Pressure         4.4 psi         (0.3 bar)           Shelter Weight         353 lbs         (160 kg)           Grid Panel Weight         170 lbs         (1.8m)           Pump Weight         13 lbs         (6 kg)           Inflator Weight         26 lbs         (12 kg)           Packaged Dimensions           Shelter         28 x 39 x 47"         (70 x 100 x 120 cm)           Grid         31 x 47 x 47"         (80 x 120 x 120 cm)           Water Requirements         23 gal per min at 58 psi         (85 liter per min at 4 bar)           Capacity         80 people per hour			
Undress Dimensions       98 x 59"       (250 x 150 cm)         Detergent Dimensions       49" x 59"       125 x 150 cm         Rinse Dimensions       49" x 59"       (125 x 150 cm)         Redress Dimensions       98" x 59"       (250 x 150 cm)         Airframe Diameter       14" )       (35 cm         Working Pressure       4.4 psi       (0.3 bar)         Shelter Weight       353 lbs       (160 kg)         Grid Panel Weight       170 lbs       (1.8m)         Pump Weight       13 lbs       (6 kg)         Inflator Weight       26 lbs       (12 kg)         Packaged Dimensions         Shelter       28 x 39 x 47"       (70 x 100 x 120 cm)         Grid       31 x 47 x 47"       (80 x 120 x 120 cm)         Water Requirements       23 gal per min at 58 psi       (85 liter per min at 4 bar)	Shelter Dimensions	24'11" x 17'9" x 8'6"	(7.6 x 5.4 x 2.6 m)
Detergent Dimensions       49" x 59"       125 x 150 cm         Rinse Dimensions       49" x 59"       (125 x 150 cm)         Redress Dimensions       98" x 59"       (250 x 150 cm)         Airframe Diameter       14" )       (35 cm         Working Pressure       4.4 psi       (0.3 bar)         Shelter Weight       353 lbs       (160 kg)         Grid Panel Weight       170 lbs       (1.8m)         Pump Weight       13 lbs       (6 kg)         Inflator Weight       26 lbs       (12 kg)         Packaged Dimensions         Shelter       28 x 39 x 47"       (70 x 100 x 120 cm)         Grid       31 x 47 x 47"       (80 x 120 x 120 cm)         Water Requirements       23 gal per min at 58 psi       (85 liter per min at 4 bar)	Door Dimensions	3'11" x 6'1"	(1 x 2.1 m)
Rinse Dimensions       49" x 59"       (125 x 150 cm)         Redress Dimensions       98" x 59"       (250 x 150 cm)         Airframe Diameter       14" )       (35 cm         Working Pressure       4.4 psi       (0.3 bar)         Shelter Weight       353 lbs       (160 kg)         Grid Panel Weight       170 lbs       (1.8m)         Pump Weight       13 lbs       (6 kg)         Inflator Weight       26 lbs       (12 kg)         Packaged Dimensions         Shelter       28 x 39 x 47"       (70 x 100 x 120 cm)         Grid       31 x 47 x 47"       (80 x 120 x 120 cm)         Water Requirements       23 gal per min at 58 psi       (85 liter per min at 4 bar)	Undress Dimensions	98 x 59"	(250 x 150 cm)
Redress Dimensions       98" x 59"       (250 x 150 cm)         Airframe Diameter       14" )       (35 cm         Working Pressure       4.4 psi       (0.3 bar)         Shelter Weight       353 lbs       (160 kg)         Grid Panel Weight       170 lbs       (1.8m)         Pump Weight       13 lbs       (6 kg)         Inflator Weight       26 lbs       (12 kg)         Packaged Dimensions         Shelter       28 x 39 x 47"       (70 x 100 x 120 cm)         Grid       31 x 47 x 47"       (80 x 120 x 120 cm)         Water Requirements       23 gal per min at 58 psi       (85 liter per min at 4 bar)	Detergent Dimensions	49" x 59"	125 x 150 cm
Airframe Diameter       14" )       (35 cm         Working Pressure       4.4 psi       (0.3 bar)         Shelter Weight       353 lbs       (160 kg)         Grid Panel Weight       170 lbs       (1.8m)         Pump Weight       13 lbs       (6 kg)         Inflator Weight       26 lbs       (12 kg)         Packaged Dimensions         Shelter       28 x 39 x 47"       (70 x 100 x 120 cm)         Grid       31 x 47 x 47"       (80 x 120 x 120 cm)         Water Requirements       23 gal per min at 58 psi       (85 liter per min at 4 bar)	Rinse Dimensions	49" x 59"	(125 x 150 cm)
Working Pressure         4.4 psi         (0.3 bar)           Shelter Weight         353 lbs         (160 kg)           Grid Panel Weight         170 lbs         (1.8m)           Pump Weight         13 lbs         (6 kg)           Inflator Weight         26 lbs         (12 kg)           Packaged Dimensions         (70 x 100 x 120 cm)           Grid         31 x 47 x 47"         (80 x 120 x 120 cm)           Water Requirements         23 gal per min at 58 psi         (85 liter per min at 4 bar)	Redress Dimensions	98" x 59"	(250 x 150 cm)
Shelter Weight         353 lbs         (160 kg)           Grid Panel Weight         170 lbs         (1.8m)           Pump Weight         13 lbs         (6 kg)           Inflator Weight         26 lbs         (12 kg)           Packaged Dimensions         Shelter         28 x 39 x 47"         (70 x 100 x 120 cm)           Grid         31 x 47 x 47"         (80 x 120 x 120 cm)           Water Requirements         23 gal per min at 58 psi         (85 liter per min at 4 bar)	Airframe Diameter	14")	(35 cm
Grid Panel Weight         170 lbs         (1.8m)           Pump Weight         13 lbs         (6 kg)           Inflator Weight         26 lbs         (12 kg)           Packaged Dimensions           Shelter         28 x 39 x 47"         (70 x 100 x 120 cm)           Grid         31 x 47 x 47"         (80 x 120 x 120 cm)           Water Requirements         23 gal per min at 58 psi         (85 liter per min at 4 bar)	Working Pressure	4.4 psi	(0.3 bar)
Pump Weight         13 lbs         (6 kg)           Inflator Weight         26 lbs         (12 kg)           Packaged Dimensions           Shelter         28 x 39 x 47"         (70 x 100 x 120 cm)           Grid         31 x 47 x 47"         (80 x 120 x 120 cm)           Water Requirements         23 gal per min at 58 psi         (85 liter per min at 4 bar)	Shelter Weight	353 lbs	(160 kg)
Inflator Weight         26 lbs         (12 kg)           Packaged Dimensions         Shelter         28 x 39 x 47"         (70 x 100 x 120 cm)           Grid         31 x 47 x 47"         (80 x 120 x 120 cm)           Water Requirements         23 gal per min at 58 psi         (85 liter per min at 4 bar)	Grid Panel Weight	170 lbs	(1.8m)
Packaged Dimensions           Shelter         28 x 39 x 47"         (70 x 100 x 120 cm)           Grid         31 x 47 x 47"         (80 x 120 x 120 cm)           Water Requirements         23 gal per min at 58 psi         (85 liter per min at 4 bar)	Pump Weight	13 lbs	(6 kg)
Shelter         28 x 39 x 47"         (70 x 100 x 120 cm)           Grid         31 x 47 x 47"         (80 x 120 x 120 cm)           Water Requirements         23 gal per min at 58 psi         (85 liter per min at 4 bar)	Inflator Weight	26 lbs	(12 kg)
Grid 31 x 47 x 47" (80 x 120 x 120 cm)  Water Requirements 23 gal per min at 58 psi (85 liter per min at 4 bar)	Packaged Dimensions		
Water Requirements 23 gal per min at 58 psi (85 liter per min at 4 bar)	Shelter	28 x 39 x 47"	(70 x 100 x 120 cm)
	Grid	31 x 47 x 47"	(80 x 120 x 120 cm)
Capacity 80 people per hour	Water Requirements	23 gal per min at 58 psi	(85 liter per min at 4 bar)
	Capacity	80 people per hour	

## **Recommended Support Systems**

- · Hot Water Generator
- Detergent Injector
- Water Ballast Tanks
- $\boldsymbol{\cdot} \, \text{Stretcher Conveyor} \,$
- Lighting

