



## HARD FLOORING

### Features and Benefits

- Provides a clean and stable platform
- Allows gurneys, wheelchairs and other equipment to roll easily across the smooth, even flooring surface
- Custom-sized to fit shelters and vestibules
- Hinged sections are secured with simple hook-and-loop seam connections for easy installation

### Specifications

Product Number	S0-FL1935	S0-FL20	S0-FL2360	S0-FLV
Fits Shelter	1935	20	2360	Vestibule Connector/Entryway
Dimensions	18' 7" x 33' 11" (5.7 x 10.4 m)	18' 7" x 18' 7" (5.7 x 5.7 m)	22' 8" x 60' 1" (5.7 x 10.4 m)	7' 8" x 7' 4" (2.3 x 2.2 m)
Total Weight	488 lbs (221.3 kg)	245 lbs (111.1 kg)	1195 lbs (542 kg)	54 lbs (24.5 kg)
Number Of Sections	7	4	12	2
Thickness	0.5" (1.3 cm)	0.5" (1.3 cm)	0.5" (1.3 cm)	0.5" (1.3 cm)
Load Strength	500 psi	500 psi	500 psi	500 psi
Fire Resistance	UL94HB	UL94HB	UL94HB	UL94HB
Temperature Use	-35 to 200 F°	-35 to 200 F°	-35 to 200 F°	35 to 200 F

