



HARD FLOORING

Features and Benefits

- Rigid flooring system provides a strong and stable floor underneath the traditional Western Shelters
- Stacks flat and interlocks for stable load
- Approximately half the cubic displacement of two inch sheet version at approximately two-thirds the weight (SO-FL20BT1)
- Fast installation: no additional connectors, tools or training required
- Sheets self-align. Steel pins allow positive sheet connection (SO-FL20BT1)
- Flooring sheets are supplied on re-usable pallets with ratchet straps
- All one inch sheet components are modular, durable, interchangeable, and designed for repeated use
- Will support light vehicles



Specifications

Part Number	One Inch Bike Track Flooring SO-FL1935BT1	One Inch Bike Track Flooring SO-FL2342BT1	One Inch Bike Track Flooring SO-FL2360BT1	Once Inch Vestibule Flooring SO-FLVCBT1
Fits Shelter	1935 Shelter System	2342 Shelter System	2360 Shelter System	Vestibule Connector
Number of Tiles	50	95	108	9
Usable Area	20'x35' 700 ft ² (65 m ²)	24'x43' 1,275 ft ² (118.4 m ²)	24'x63' 1,512 ft ² (213 m ²)	126 ft ² (128 m ²)
Weight	1350 lbs (612.3 kg)	2489 lbs (1128.9 kg)	2916 lbs (1322.6 kg)	235 lbs (106.5 kg)
Packaged Dimensions	32 x 42 x 48" (0.8 x 1 x 1.2 m)	32 x 42 x 48" (0.8 x 1 x 1.2 m)	32 x 42 x 48" (0.8 x 1 x 1.2 m)	9 x 42 x 48" (0.2 x 1 x 1.2 m)
Tile Dimensions	1 x 42 x 48" (0.03 x 0.6 x 1.2 m)	1 x 42 x 48" (0.03 x 0.6 x 1.2 m)	1 x 42 x 48" (0.03 x 0.6 x 1.2 m)	1 x 42 x 48" (0.03 x 0.6 x 1.2 m)
Material	High density polyethylene	High density polyethylene	High density polyethylene	High density polyethylene
Color	Desert Sand	Desert Sand	Desert Sand	Desert Sand

*Two Inch Shelter flooring can be configured for In-Floor Cable Management system (ICM)