



Scout Hub I

The Scout Hub I gives you the flexibility to set up a stand-alone tent or develop a centralized space for your growing complex. Up to four strategic connection points are accessible in this design.

Key Features and Benefits

- Stand alone or centralized structure
- Lightweight-frame
- Easy to erect
- Seamless, watertight transitions
- Multi-configuration connections
- Rugged and durable

Works with

- Any Scout series shelters
- All of the Scout system
- Extreme weather liner
- HVAC
- Other brand RDS
- Add-on assets like monitor brackets

Set-up and Strike Team

- **Scout Hub I** (alone)
3 person minimum / 4 preferred <30 minutes

Fabric

meets U.S. Military guidelines

- USIFI-PRF-44103
- USIFI-PRF-20696

Colors

Camo Green 483 | Desert Tan 459 | Custom options

Scout Hub I Specifications

SCOUT HUB I SPECIFICATIONS	
Overall Dimensions	22.03x22.03x11.30ft (6.71x6.71x3.44m)
Usable Area	473ft ² (43.94m ²)
Internal Volume	3795ft ³ (107.46m ³)
With Insulation	3100 ft ³ (87.78m ³)

SCOUT HUB I COMPONENTS	
Windows	(8) 38 x 38 in (96.52 x 96.52 cm) Hook & loop closure, roll-up tie-offs, and vector mesh screen
ECU Duct Ports	(8) 16 in (40.64 cm) Diameter with elastic sock
Doorways	(4) 48 x 84 in (121.92 x 213.36 cm) Double-zippered closure with double-sided hook & loop connection boot
Wind Line Tie Off Points	(8) Frame hardpoint connections with seatbelt strap
Insulation Air Gap Vent	(1) Per end wall with hook & loop closure
Usable Area	441 ft ² (37.16 m ²)
Height at Peak	10 ft (3.05 m)
Doors	1/wall
Windows	2/wall
ECU Ducts	4 sets

SNOW AND RAIN LOAD	
Snow 10lb /ft ² (48.82 kg/m ²)	Rain 2in/hr (50.80 mm/hr)

WIND RATING	
Sustained winds of 65-75mph gusts (104kmh / 120kmh)	
Total Packed Weight	800lb (362.9)

SCOUT HUB I PART NUMBERS	
Hub Only	SC-2222H
Hub with Liner and Floor	SC-2222HK